



Micro Commercial Components
 21201 Itasca Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

1N34A

Germanium Diode 65 Volt

Features

- Low Leakage Current
- Flat Junction Capacitance
- High Mechanical Strength

Maximum Ratings

- Operating Temperature: -65°C to +75°C
- Storage Temperature: -65°C to +75°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Peak Inverse Voltage	PIV	65V	$I_R=1.0mA$
Average Rectified Current	I_o	50mA	
Peak Forward Surge Current	I_{FSM}	500mA	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F	1.00V	$I_{FM} = 5.0mA$; $T_J = 25^\circ C^*$
Maximum Reverse Current	I_R	30uA 500uA	$T_A = 25^\circ C$ $V_R=10V$ $V_R=50V$
Typical Junction Capacitance	C_J	0.8pF	Measured at 1.0MHz, $V_R=0V$

*Pulse test: Pulse width 300 usec, Duty cycle 2%

DO-7

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	-----	.300	-----	7.62	
B	-----	.107	-----	2.72	∅
C	.018	.022	0.46	0.56	∅
D	1.000	-----	25.40	-----	

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.